NSN 5306-00-165-2182

Eye Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-165-2182

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
1.660 inches
Eye Inside Diameter:
Between 0.6249 inches and 0.6254 inches
Shoulder Thickness:
0.190 inches
Shank Length:
2.250 inches
Eye Stock Diameter:
0.197 inches
Shoulder Diameter:
0.750 inches
Overall Length:
3.437 inches
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
Tilleady dty Fer Illon (tpi).
24
24
24 Distance From Center Of Eye To Shank End:
Distance From Center Of Eye To Shank End: 3.000 inches
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n Is3ang25 located in eye bolt hole
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material: Steel comp 4340
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n Is3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n Is3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf Shelf Life:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf Shelf Life: N/a
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf Shelf Life: N/a
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n Is3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Distance From Center Of Eye To Shank End: 3.000 inches Eye Outside Width: 0.875 inches Special Features: Bearing fscm 73134 p/n ls3ang25 located in eye bolt hole Material: Steel comp 4340 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: