Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-168-5094

read Direction:	
ght-hand	
aread Length:	
tween 0.560 inches and 0.600 inches	
stener Length:	
080 inches	
ead Style:	
exagon	
ead Height:	
etween 0.150 inches and 0.170 inches	
idth Between Flats:	
tween 0.616 inches and 0.625 inches	
rst Diameter From Head:	
etween 0.439 inches and 0.441 inches	
econd Diameter From Head:	
etween 0.229 inches and 0.233 inches	
stance From Largest Bearing Surface Of Head To End Of First Diamete	r:
tween 0.150 inches and 0.170 inches	
stance From Largest Bearing Surface Of Head To End Of Second Diam	eter:
tween 2.480 inches and 2.520 inches	
read Diameter:	
312 inches	
onstandard Thread Pitch Diameter:	
.2830 to 0.2849 inches	
rready Qty Per Inch (tpi):	
ardness Rating:	
.0 rockwell c and 32.0 rockwell c	
ternally Relieved Body Diameter Quantity:	
aterial:	
eel comp 8740	
aterial Specification:	
ns 6322 assn standard single material response	
read Series Designator:	
- If	
nelf Life:	
a	
nit Of Measure:	
emilitarization:	

NSN 5306-00-168-5094

Externally Relieved Body Bolt - Page 2 of 2

Fiig: A003b0

