

View Online at <https://aerobasegroup.com/nsn/5306-00-172-7165>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.586 inches and 0.636 inches

Fastener Length:

Between 1.721 inches and 1.751 inches

Head Style:

Double hexagon w/hole

Head Height:

0.319 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

0.050 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium or nickel and cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, cl 3 military specification 1st treatment response or ams 2416 assn standard 2nd treatment response or ams 2416 assn standard 3rd treatment response

Thread Series Designator:

Unjf

Specification Data:

56878-ewb26 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.