# NSN 5306-00-174-4657

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-174-4657



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.630 inches and 0.690 inches

### Fastener Length:

1.250 inches

#### **Head Style:**

Double hexagon w/hole

#### **Head Height:**

0.260 inches

#### Width Between Flats:

0.250 inches

#### Extended Washer Diameter:

0.375 inches

#### **Extended Washer Thickness:**

0.040 inches

#### Hole Diameter:

0.047 inches

### Thread Diameter:

0.190 inches

### Grip Length:

Between 0.630 inches and 0.690 inches

#### Hole Quantity:

4

### Hole Type:

Drilled

#### **Features Provided:**

Finished head

### Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

130000 pounds per square inch

## Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

## Minimum Yield Strength:

85000 pounds per square inch

## Hole Configuration Style:

Double hexagon longitudinal hole

## Surface Finish:

32.0 microinches threads

# NSN 5306-00-174-4657

Machine Bolt - Page 2 of 2

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

