## NSN 5306-00-177-5506

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-177-5506 **Thread Class:** 

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.625 inches and 0.665 inches
Fastener Length:
Between 3.635 inches and 3.655 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.990 inches and 3.010 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches primary washer
Material:
Steel
Material Specification:
Mil-s-5626 military specification single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5306-00-177-5506

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.