## NSN 5306-00-177-5587



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-177-5587 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.423 inches and 0.473 inches **Fastener Length:** Between 0.890 inches and 0.910 inches **Head Style:** Hexagon **Head Height:** Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Shoulder Diameter:** 0.340 inches and 0.350 inches first shoulder **Shoulder Length:** 0.385 inches and 0.395 inches first shoulder **Hole Diameter:** 0.070 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 rockwell b and 341.0 rockwell b Minimum Yield Strength: 85000 pounds per square inch **Hole Configuration Style:** Hexagon flats **Shoulder Shape:** Round first shoulder

**Product Name:** Navy special project Material: Iron alloy 660

## NSN 5306-00-177-5587

Shoulder Bolt - Page 2 of 2



Material Specification:
-------------------------

Ams 5732 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0