## NSN 5306-00-177-5602

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-177-5602

Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.930 inches and 1.000 inches				
Fastener Length:				
1.750 inches				
Head Style:				
Pan no. 2				
Head Diameter:				
0.800 inches				
Head Height:				
0.250 inches				
Shoulder Diameter:				
0.532 inches first shoulder and 0.535 inches first shoulder				
Shoulder Length:				
0.690 inches first shoulder and 0.700 inches first shoulder				
Rib Major Diameter:				
Between 0.550 inches and 0.560 inches				
Rib Length:				
0.125 inches				
Rib Minor Diameter:				
Between 0.532 inches and 0.545 inches				
Rib Quantity:				
35				
Thread Diameter:				
0.500 inches				
Features Provided:				
Casehardened				
Thready Qty Per Inch (tpi):				
20				
Shoulder Shape:				
Round first shoulder				
Material:				
Steel comp 1335 or steel comp 4037 or steel comp 4140 or steel comp 8640				
Material Specification:				
Qq-s-633, cond anl federal specification all material responses				
Surface Treatment:				
Cadmium and chromate				
Surface Treatment Specification:				

Qq-p-416, cl 3 federal specification all treatment responses

## NSN 5306-00-177-5602

Ribbed Shoulder Bolt - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	<b>D</b> C3	igilatoi.

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0