NSN 5306-00-177-5602

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-177-5602

| Thread Class: | | | | | |
|--|--|--|--|--|--|
| 3a | | | | | |
| Thread Direction: | | | | | |
| Right-hand | | | | | |
| Thread Length: | | | | | |
| Between 0.930 inches and 1.000 inches | | | | | |
| Fastener Length: | | | | | |
| 1.750 inches | | | | | |
| Head Style: | | | | | |
| Pan no. 2 | | | | | |
| Head Diameter: | | | | | |
| 0.800 inches | | | | | |
| Head Height: | | | | | |
| 0.250 inches | | | | | |
| Shoulder Diameter: | | | | | |
| 0.532 inches first shoulder and 0.535 inches first shoulder | | | | | |
| Shoulder Length: | | | | | |
| 0.690 inches first shoulder and 0.700 inches first shoulder | | | | | |
| Rib Major Diameter: | | | | | |
| Between 0.550 inches and 0.560 inches | | | | | |
| Rib Length: | | | | | |
| 0.125 inches | | | | | |
| Rib Minor Diameter: | | | | | |
| Between 0.532 inches and 0.545 inches | | | | | |
| Rib Quantity: | | | | | |
| 35 | | | | | |
| Thread Diameter: | | | | | |
| 0.500 inches | | | | | |
| Features Provided: | | | | | |
| Casehardened | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 20 | | | | | |
| Shoulder Shape: | | | | | |
| Round first shoulder | | | | | |
| Material: | | | | | |
| Steel comp 1335 or steel comp 4037 or steel comp 4140 or steel comp 8640 | | | | | |
| Material Specification: | | | | | |
| Qq-s-633, cond anl federal specification all material responses | | | | | |
| Surface Treatment: | | | | | |
| Cadmium and chromate | | | | | |
| Surface Treatment Specification: | | | | | |

Qq-p-416, cl 3 federal specification all treatment responses

NSN 5306-00-177-5602

Ribbed Shoulder Bolt - Page 2 of 2



| _ | | • | _ | |
|---|-------|---------|------|-----------|
| 1 | hread | Series | 1)66 | ignator: |
| • | mcaa | OCI ICS | 000 | igilatoi. |

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0