## NSN 5306-00-177-5747

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-177-5747 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.504 inches and 0.595 inches **Fastener Length:** Between 0.919 inches and 0.959 inches **Head Style:** Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.615 inches and 0.627 inches **Shoulder Diameter:** 0.4330 inches first shoulder and 0.4370 inches first shoulder **Shoulder Length:** 0.322 inches first shoulder and 0.332 inches first shoulder **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 or steel comp 4130 or steel comp 4037 or steel comp 8740 or steel comp 8630 or steel comp 8735 **Surface Treatment:** Chromate **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1297 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5306-00-177-5747** Shoulder Bolt - Page 2 of 2



Fiig:

A003b0