

View Online at <https://aerobasegroup.com/nsn/5306-00-180-0363>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.626 inches and 0.703 inches

Fastener Length:

Between 2.828 inches and 2.875 inches

Head Style:

Hexagon

Head Height:

Between 0.234 inches and 0.266 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Grip Diameter:

Between 0.4362 inches and 0.4367 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 2.172 inches and 2.202 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.672 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp 8740 or steel comp 8735 or steel comp 4140 or steel comp 4130 or steel comp 8630

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mils-s-6758 military specification 4th material response and mil-s-6050 military specification 5th material response or ams 6300 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.