## NSN 5306-00-180-0530

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-180-0530 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.641 inches **Fastener Length:** Between 5.437 inches and 5.484 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 4.796 inches and 4.843 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 5.437 inches first hole and 5.484 inches first hole Material: Steel **Surface Treatment:** Cadmium and dichromate **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## **NSN 5306-00-180-0530** Machine Bolt - Page 2 of 2



Fiig:

A003b0