NSN 5306-00-180-3366

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-180-3366

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.531 inches
Fastener Length:
Between 1.891 inches and 1.938 inches
Head Style:
Hexagon
Head Height:
0.219 inches
Width Between Flats:
Between 0.428 inches and 0.440 inches
Hole Diameter:
0.188 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.360 inches and 1.407 inches
Hole Quantity:
6
6 Hole Type:
Hole Type:
Hole Type: Drilled
Hole Type: Drilled Features Provided:
Hole Type: Drilled Features Provided: Finished head
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi):
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi):
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment: Cadmium and dichromate
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Surface Treatment: Cadmium and dichromate Thread Series Designator:

NSN 5306-00-180-3366

Machine Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0