NSN 5306-00-182-1866

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-182-1866

| view Offilite at https://aerobasegroup.com/hsh/3300-00-102 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.438 inches and 0.515 inches |
| Fastener Length: |
| Between 2.141 inches and 2.188 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.140 inches and 0.172 inches |
| Width Between Flats: |
| Between 0.428 inches and 0.440 inches |
| Hole Diameter: |
| 0.046 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.672 inches and 1.703 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Steel comp 431 |
| Material Specification: |
| Mil-s-18732 military specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |

Unf

NSN 5306-00-182-1866

Machine Bolt - Page 2 of 2



| Shelf L | ife: |
|---------|------|
|---------|------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.