
## NSN 5306-00-182-1947

Machine Bolt - Page 1 of 2

**Thread Class:** 





## 3a **Thread Direction: Right-hand Thread Length:** Between 0.375 inches and 0.453 inches Fastener Length: Between 2.266 inches and 2.312 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches **Thread Diameter:** 0.190 inches Grip Length: Between 1.859 inches and 1.891 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response Surface Treatment: Passivate **Thread Series Designator:**

Unf

## NSN 5306-00-182-1947

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-s-18732 spec.

