## NSN 5306-00-182-2035

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-182-2035

| Thread Class:  3a  Thread Direction:  Right-hand                 |
|--|
| Thread Direction:  |
|  |
| Right-hand   |
| •  |
| Thread Length:   |
| 0.532 inches   |
| Fastener Length:   |
| 3.344 inches   |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.172 inches and 0.204 inches                            |
| Width Between Flats:   |
| Between 0.490 inches and 0.502 inches                            |
| Shank Unthreaded Hole Diameter:                                  |
| 0.076 inches first hole  |
| Thread Diameter:   |
| 0.312 inches   |
| Grip Length:   |
| 2.812 inches   |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):                                      |
| 24   |
| Min. Tensile Strength (psi):                                     |
| 125000 pounds per square inch                                    |
| Hardness Rating:   |
| 26.0 rockwell c and 32.0 rockwell c                              |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 3.171 inches first hole  |
| Material:  |
| Stainless steel  |
| Material Specification:  |
| Qq-s-770 federal specification single material response          |
| Surface Treatment:   |
| Passivate  |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5306-00-182-2035

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0