## NSN 5306-00-182-9529

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-182-9529
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.602 inches and 0.662 inches
Fastener Length:
Between 1.117 inches and 1.147 inches
Head Style:
Hexagon
Head Height:
Between 0.172 inches and 0.204 inches
Width Between Flats:
Between 0.492 inches and 0.501 inches
Hole Diameter:
0.076 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.485 inches and 0.515 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Hole Configuration Style:
Hexagon flats
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd materia
response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-00-182-9529

Machine Bolt - Page 2 of 2



Specification Data:
80205-nas1005 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Domilitarization:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.