# NSN 5306-00-182-9588

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-182-9588



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 1.000 inches and 1.050 inches

#### Fastener Length:

Between 3.135 inches and 3.165 inches

**Head Style:** 

Double hexagon w/hole

**Head Height:** 

0.600 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

#### **Extended Washer Diameter:**

Between 1.045 inches and 1.055 inches

#### **Extended Washer Thickness:**

0.118 inches

#### **Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

# **Thread Diameter:**

0.562 inches

Grip Length:

Between 2.115 inches and 2.135 inches

### Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

260000 pounds per square inch

# Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

### Material:

Steel comp h11

### Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Mil-c-8837 type 1, cl 2 military specification single treatment response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-00-182-9588

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

