

View Online at <https://aerobasegroup.com/nsn/5306-00-182-9588>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.000 inches and 1.050 inches

**Fastener Length:**

Between 3.135 inches and 3.165 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.600 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Extended Washer Diameter:**

Between 1.045 inches and 1.055 inches

**Extended Washer Thickness:**

0.118 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 2.115 inches and 2.135 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837 type 1, cl 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.