NSN 5306-00-187-9884

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-187-9884 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.050 inches **Fastener Length:** 5.500 inches **Head Style:** Hexagon **Head Height:** Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches **First Diameter From Head:** 0.500 inches **Second Diameter From Head:** Between 0.433 inches and 0.443 inches **Third Diameter From Head:** 0.500 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.900 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 3.166 inches and 3.170 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 4.250 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Thread Series Designator:**

Unf

NSN 5306-00-187-9884

Externally Relieved Body Bolt - Page 2 of 2



	L -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0