NSN 5306-00-194-3206

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-194-3206

·
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.968 inches and 1.047 inches
Fastener Length:
Between 2.172 inches and 2.219 inches
Head Style:
Hexagon
Head Height:
Between 0.453 inches and 0.484 inches
Width Between Flats:
Between 0.928 inches and 0.939 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 1.172 inches and 1.204 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unc

NSN 5306-00-194-3206

Machine Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0