## NSN 5306-00-194-5804

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-194-5804 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.387 inches and 0.467 inches **Fastener Length:** Between 1.052 inches and 1.072 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.605 inches and 0.665 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-00-194-5804

Machine Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0