NSN 5306-00-195-2303

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-195-2303 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.778 inches and 0.798 inches **Fastener Length: 3.538** inches **Head Style:** Double hexagon w/hole **Head Height:** 0.504 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** 0.123 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.740 inches and 2.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4140 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5306-00-195-2303

Shear Bolt - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0