

View Online at <https://aerobasegroup.com/nsn/5306-00-197-3266>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.384 inches and 0.431 inches

**Fastener Length:**

Between 2.634 inches and 2.681 inches

**Head Style:**

Double hexagon

**Head Height:**

0.210 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

2.250 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

132000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.501 inches first hole and 2.533 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Stainless steel

**Material Specification:**

H-11 stsbs000 fscm 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Stsbs000 fscm 98897 mfr ref all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0