## NSN 5306-00-197-3266



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-197-3266 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.384 inches and 0.431 inches **Fastener Length:** Between 2.634 inches and 2.681 inches **Head Style:** Double hexagon **Head Height:** 0.210 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** 2.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 132000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.501 inches first hole and 2.533 inches first hole **Surface Finish:** 63.0 microinches grip Material: Stainless steel **Material Specification:** H-11 stsbs000 fscm 98897 mfr ref single material response **Surface Treatment:** Nickel and cadmium and chromate **Surface Treatment Specification:** Stsbs000 fscm 98897 mfr ref all treatment responses **Thread Series Designator:** Unjf

Shelf Life:

N/a

## **NSN 5306-00-197-3266**Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A003b0