## NSN 5306-00-197-5947

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-197-5947

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.389 inches and 0.511 inches  |
| Fastener Length:   |
| Between 1.466 inches and 1.496 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.109 inches and 0.141 inches  |
| Width Between Flats:   |
| Between 0.367 inches and 0.376 inches  |
| Hole Diameter:   |
| 0.046 inches   |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.985 inches and 1.015 inches  |
| Hole Quantity:   |
| 1  |
| Hole Type:   |
| Drilled  |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 140000 pounds per square inch  |
| Hole Configuration Style:  |
| Hexagon flats  |
| Material:  |
| Steel or iron alloy 660  |
| Material Specification:  |
| Ams5732 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Mil-s-5002 military specification single treatment response                                      |
| Thread Series Designator:  |
| Line.  |

Unf

## NSN 5306-00-197-5947

Machine Bolt - Page 2 of 2



| Specification Data:  |
|--|
| 80205-nas1003 professional/industrial association standard |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

Mil-std (military Standard):

Mil-s-5002 spec.

A003b0