NSN 5306-00-198-9437

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-198-9437

View Online at https://aerobasegroup.com/nsn/5306-00-198-9437
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.309 inches and 0.359 inches
Fastener Length:
Between 1.444 inches and 1.474 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.265 inches and 0.285 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.340 inches and 0.350 inches
Extended Washer Thickness:
Between 0.054 inches and 0.074 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard 1st material response or ams6487 assn standard 2nd material response
Surface Treatment:
Cadmium

Cadmium

NSN 5306-00-198-9437

Shear Bolt - Page 2 of 2



Surface Treatment Speci

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0