

View Online at <https://aerobasegroup.com/nsn/5306-00-202-0114>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.357 inches and 0.393 inches

Fastener Length:

Between 1.435 inches and 1.455 inches

Head Style:

Dished hexagon

Head Height:

Between 0.095 inches and 0.110 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1885 inches and 0.1894 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 1.062 inches and 1.078 inches

Thready Qty Per Inch (tpi):

31

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Surface Finish:

63.0 microinches grip

Special Features:

Impedance locking element in shank

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0