

View Online at <https://aerobasegroup.com/nsn/5306-00-202-0287>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.211 inches and 0.262 inches

Fastener Length:

Between 1.168 inches and 1.188 inches

Head Style:

Dished hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Hole Diameter:

0.045 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 0.750 inches and 0.766 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.068 inches first hole and 1.098 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Retaining element in shank

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0