NSN 5306-00-205-3383

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-205-3383

Thursd Olses
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.503 inches and 0.553 inches
Fastener Length:
Between 1.825 inches and 1.855 inches
Head Style:
Dished hexagon
Head Height:
Between 0.219 inches and 0.234 inches
Width Between Flats:
Between 0.679 inches and 0.690 inches
Hole Diameter:
0.075 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6307 professional/industrial association standard

NSN 5306-00-205-3383

Shear Bolt - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0