
## NSN 5306-00-205-3384

Shear Bolt - Page 1 of 2

3a

3

20





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.503 inches and 0.553 inches Fastener Length: Between 1.388 inches and 1.418 inches **Head Style:** Dished hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Thread Diameter:** 0.438 inches Grip Length: Between 0.865 inches and 0.875 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas6307 professional/industrial association standard

## NSN 5306-00-205-3384

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

