

View Online at <https://aerobasegroup.com/nsn/5306-00-205-3931>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.933 inches and 0.983 inches

**Fastener Length:**

Between 2.631 inches and 2.661 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.625 inches and 0.640 inches

**Width Between Flats:**

Between 1.801 inches and 1.815 inches

**Grip Diameter:**

Between 1.2475 inches and 1.2490 inches

**Thread Diameter:**

1.250 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1120 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.