

View Online at <https://aerobasegroup.com/nsn/5306-00-206-0760>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.798 inches and 0.830 inches

**Fastener Length:**

Between 2.298 inches and 2.328 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.802 inches and 0.813 inches

**Head Height:**

0.460 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.500 inches

**Width Across Flats:**

Between 0.500 inches and 0.503 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.125 inches first hole

**Special Features:**

Six drilled holes in head

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 6150

**Material Specification:**

Mil-s-5000, cond c military specification 1st material response or mil-s-6049 cond c military specification 2nd material response or mil-s-8503 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.