## NSN 5306-00-206-0816

Internal Wrenching Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-206-0816



Thread Class:
3a Thread Direction
Thread Direction:
Right-hand
Thread Length:
Between 0.797 inches and 0.827 inches
Fastener Length:
1.562 inches
Head Style:
Bevel-conical
Head Diameter:
Between 0.740 inches and 0.750 inches
Head Height:
0.407 inches
Hole Diameter:
0.062 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole
Internal Drive Style:
Hexagon
Thread Diameter:
0.438 inches
Width Across Flats:
Between 0.376 inches and 0.379 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.266 inches first hole
Material:
Steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium
Thread Series Designator:
Unjf

## NSN 5306-00-206-0816

Internal Wrenching Bolt - Page 2 of 2



**Specification Data:** 

80205-nas147 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0