

View Online at <https://aerobasegroup.com/nsn/5306-00-206-1300>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

2.062 inches

**Head Style:**

Hexagon

**Head Height:**

0.375 inches

**Width Between Flats:**

0.875 inches

**Shoulder Diameter:**

0.495 inches first shoulder and 0.500 inches first shoulder

**Shoulder Length:**

1.531 inches first shoulder

**Hole Diameter:**

0.062 inches

**Shank Unthreaded Hole Diameter:**

0.125 inches first hole

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.938 inches first hole

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Shoulder chamfered 0.016 in. Lg by 45 degrees angle at undercut end, w/offset between head and shoulder 0.062 in. Lg 0.781 in. Dia

**Material:**

Steel comp 1137

**Material Specification:**

Qq-s-637 federal specification single material response

**Surface Treatment:**

Phosphate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0