

View Online at <https://aerobasegroup.com/nsn/5306-00-206-3425>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.438 inches and 0.515 inches

**Fastener Length:**

Between 0.766 inches and 0.812 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.172 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.297 inches and 0.328 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.614 inches first hole and 0.634 inches first hole

**Material:**

Steel comp 321 or steel comp 347

**Material Specification:**

Qq-s-763 federal specification all material responses

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas501 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0