

View Online at <https://aerobasegroup.com/nsn/5306-00-206-3815>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.656 inches

**Eye Inside Diameter:**

Between 0.375 inches and 0.378 inches

**Shoulder Thickness:**

0.125 inches

**Shank Length:**

Between 2.828 inches and 2.875 inches

**Eye Stock Thickness:**

0.250 inches

**Shoulder Diameter:**

0.875 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Overall Length:**

4.063 inches

**Thread Diameter:**

0.438 inches

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Center Of Eye To Shank End:**

3.562 inches

**Distance From Threaded End To Shank Hole Center:**

2.672 inches first hole

**Eye Outside Width:**

0.875 inches

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8695 military specification 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.