

View Online at <https://aerobasegroup.com/nsn/5306-00-206-3824>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.625 inches and 0.688 inches

Eye Inside Diameter:

Between 0.375 inches and 0.378 inches

Shoulder Thickness:

Between 0.078 inches and 0.110 inches

Shank Length:

Between 0.937 inches and 0.984 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

Between 0.734 inches and 0.766 inches

Shank Unthreaded Hole Diameter:

0.096 inches first hole and 0.116 inches first hole

Overall Length:

Between 1.905 inches and 2.048 inches

Thread Diameter:

0.375 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

2.0 rockwell c and 32.0 rockwell c

Distance From Center Of Eye To Shank End:

Between 1.515 inches and 1.594 inches

Distance From Threaded End To Shank Hole Center:

0.734 inches first hole and 0.766 inches first hole

Eye Outside Width:

Between 0.734 inches and 0.766 inches

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0