NSN 5306-00-206-4276

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-206-4276

| Thread Class: |
|---|
| |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| Between 0.844 inches and 0.875 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.150 inches and 0.163 inches |
| Width Between Flats: |
| Between 0.425 inches and 0.437 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.125 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 120000 pounds per square inch |
| Hardness Rating: |
| 23.0 rockwell c and 32.0 rockwell c |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 5 assn standard single material response |
| Surface Treatment: |
| Zinc |
| Surface Treatment Specification: |
| Qq-z-325, type 3, class 2 federal specification single treatment response |
| Thread Series Designator: |
| |
| Specification Or Standard: |
| 2 type and c5 style |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5306-00-206-4276

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

