

View Online at <https://aerobasegroup.com/nsn/5306-00-206-4367>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.781 inches

**Fastener Length:**

4.969 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.265 inches and 0.297 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Hole Diameter:**

0.070 inches

**Grip Diameter:**

Between 0.4986 inches and 0.4991 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

4.188 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.609 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.