NSN 5306-00-206-4931

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-206-4931

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.406 inches
Fastener Length:
Between 0.453 inches and 0.500 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.428 inches and 0.440 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.046 inches and 0.078 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Material:
Steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
81349-mil-b-6812 government specification and 88044-an4-3a/canceled government standard
Specification Or Standard:
Hex type and 1/4 unf size and 1/2 in. Length
DEX IVOE AND 1/4 UNI SIZE AND 1/2 IN LENGTH

N/a

NSN 5306-00-206-4931

Machine Bolt - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6098 spec.