## NSN 5306-00-206-6340



Ribbed Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-206-6340 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** 2.562 inches **Head Style:** Flat chamfer **Head Diameter:** 1.312 inches **Head Height:** 0.312 inches **Shoulder Diameter:** 0.973 inches first shoulder and 0.977 inches first shoulder **Shoulder Length:** 0.938 inches first shoulder **Rib Major Diameter:** Between 1.020 inches and 1.023 inches Rib Length: 0.438 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.281 inches **Rib Minor Diameter:** Between 0.930 inches and 0.945 inches **Rib Quantity:** 36 **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): **Rib Included Angle:** 90.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 8620 or steel comp 4620 or steel comp 8622 or steel comp 4427 **Surface Treatment:** Cadmium

Unf

**Thread Series Designator:** 

## NSN 5306-00-206-6340

Ribbed Shoulder Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0