

View Online at <https://aerobasegroup.com/nsn/5306-00-206-7667>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 2.490 inches and 2.510 inches

Fastener Length:

Between 3.490 inches and 3.510 inches

Head Style:

Tee no. 3

Head Height:

Between 0.150 inches and 0.170 inches

Head Length:

Between 0.420 inches and 0.440 inches

Width Between Flats:

Between 0.370 inches and 0.390 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Material:

Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6758 military specification 4th material response

Surface Treatment:

Cadmium and chromate or zinc

Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification 1st treatment response and qq-p-416 type 2 class 3 federal specification 2nd treatment response or qq-z-325 type 1 class 3 federal specification 3rd treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas284 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6098 spec.