

View Online at <https://aerobasegroup.com/nsn/5306-00-206-9341>

Thread Direction:

Right-hand

Thread Length:

0.540 inches

Fastener Length:

Between 0.930 inches and 0.950 inches

Head Style:

Double hexagon extended washer

Head Height:

0.416 inches

Width Between Flats:

Between 0.424 inches and 0.439 inches

Extended Washer Diameter:

0.572 inches

Extended Washer Thickness:

0.100 inches

Shoulder Diameter:

0.429 inches first shoulder

Shoulder Length:

0.410 inches first shoulder

Hole Diameter:

0.047 inches

Thread Diameter:

0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.2797/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

136000 pounds per square inch

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Double hexagon flats

Shoulder Shape:

Round first shoulder

Special Features:

Head counterbored 0.268 in. Diameter 0.204 in. Depth

Material:

Steel

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0