

View Online at <https://aerobasegroup.com/nsn/5306-00-206-9341>

**Thread Direction:**

Right-hand

**Thread Length:**

0.540 inches

**Fastener Length:**

Between 0.930 inches and 0.950 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.416 inches

**Width Between Flats:**

Between 0.424 inches and 0.439 inches

**Extended Washer Diameter:**

0.572 inches

**Extended Washer Thickness:**

0.100 inches

**Shoulder Diameter:**

0.429 inches first shoulder

**Shoulder Length:**

0.410 inches first shoulder

**Hole Diameter:**

0.047 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Nonstandard Thread Pitch Diameter:**

+0.2797/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

136000 pounds per square inch

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Hole Configuration Style:**

Double hexagon flats

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Head counterbored 0.268 in. Diameter 0.204 in. Depth

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0