NSN 5306-00-206-9653

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-206-9653 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.812 inches **Fastener Length:** Between 3.797 inches and 3.827 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.802 inches and 0.813 inches **Head Height:** 0.460 inches **Hole Diameter:** 0.055 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.111 inches first hole **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.5005 inches and 0.5035 inches **Hole Quantity:** 6 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round Distance From Head Largest Bearing Surface To Shank Hole Center: 3.625 inches first hole Material: Steel **Surface Treatment:** Cadmium

Unf

Thread Series Designator:

NSN 5306-00-206-9653

Internal Wrenching Bolt - Page 2 of 2



| - | | | | |
|----|----|-----|------|--|
| ٠. | hΔ | Iŧ. | ife: | |
| | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0