

View Online at <https://aerobasegroup.com/nsn/5306-00-206-9655>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.923 inches and 0.938 inches

Fastener Length:

Between 4.923 inches and 4.953 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.988 inches and 1.000 inches

Head Height:

0.595 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.563 inches and 0.566 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.750 inches first hole

Special Features:

Six drilled holes in head

Material:

Steel comp 4140 or steel comp 6150 or steel comp 8740 or steel comp 3140

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503, cond, c4 military specification 3rd material response or qq-s-690, cond, e4 federal specification 4th material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Specification Data:

24062-nas150adh79 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.