

View Online at <https://aerobasegroup.com/nsn/5306-00-206-9655>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.923 inches and 0.938 inches

**Fastener Length:**

Between 4.923 inches and 4.953 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.988 inches and 1.000 inches

**Head Height:**

0.595 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.625 inches

**Width Across Flats:**

Between 0.563 inches and 0.566 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.750 inches first hole

**Special Features:**

Six drilled holes in head

**Material:**

Steel comp 4140 or steel comp 6150 or steel comp 8740 or steel comp 3140

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503, cond, c4 military specification 3rd material response or qq-s-690, cond, e4 federal specification 4th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Specification Data:**

24062-nas150adh79 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.