Externally Relieved Body Bolt - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5306-00-206-9997

Thread Class:
Thread Direction:
Right-hand
Thread Length:
Between 0.608 inches and 0.748 inches
Fastener Length: 1.288 inches
Head Style: Dee chamfer
Head Diameter:
Between 0.610 inches and 0.630 inches
Head Height:
Between 0.240 inches and 0.260 inches
Distance From Centerline To Flat:
Between 0.247 inches and 0.253 inches
Hole Diameter:
0.062 inches
First Diameter From Head:
Between 0.309 inches and 0.312 inches
Second Diameter From Head:
Between 0.235 inches and 0.245 inches
Third Diameter From Head:
Between 0.309 inches and 0.312 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.210 inches and 0.230 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.280 inches and 0.320 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
Between 0.480 inches and 0.540 inches
Thread Diameter:
0.312 inches
Hole Quantity:
1
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
24
Hole Configuration Style:
Round
Externally Relieved Body Diameter Quantity:
3

3

NSN 5306-00-206-9997

Externally Relieved Body Bolt - Page 2 of 2



Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0