NSN 5306-00-207-2436

Machine Bolt - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5306-00-207-2436

Т	hread Class:
2;	a
Т	hread Direction:
R	ight-hand
Т	hread Length:
1.	.312 inches
F	astener Length:
3.	.500 inches
Н	lead Style:
Н	lexagon
н	ead Height:
0.	.243 inches
W	/idth Between Flats:
0.	.562 inches
s	hank Unthreaded Hole Diameter:
0.	.125 inches first hole
Т	hread Diameter:
0.	.375 inches
G	rip Length:
2.	.187 inches
F	eatures Provided:
Fi	inished head
Т	hready Qty Per Inch (tpi):
24	4
Μ	lin. Tensile Strength (psi):
5	5 pounds per square inch
н	ardness Rating:
9	5.5 rockwell b
D	istance From Head Largest Bearing Surface To Shank Hole Center:
2.	.219 inches first hole
Μ	laterial:
S	teel
S	urface Treatment:
С	admium
Т	hread Series Designator:
U	Inf
S	helf Life:
Ν	/a
U	nit Of Measure:

NSN 5306-00-207-2436 Machine Bolt - Page 2 of 2

Fiig: A003b0

