NSN 5306-00-207-4589

Machine Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-00-207-4589



3a **Thread Direction: Right-hand Thread Length:** Between 0.563 inches and 0.594 inches Fastener Length: Between 0.625 inches and 0.687 inches **Head Style:** Crowned hexagon **Head Height:** 0.141 inches Width Between Flats: Between 0.428 inches and 0.460 inches Hole Diameter: 0.062 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.031 inches and 0.062 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unf

NSN 5306-00-207-4589

Machine Bolt - Page 2 of 2



Specification Data:

80205-nas428 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0